

Table of contents

ELT

Luminaire parts list..... 2



**Site 1**

    Results summary of surfaces..... 3

    Piebraucamais ceļš / Perpendicular illuminance (adaptive)..... 4


    NAI iekārtu laukums / Perpendicular illuminance (adaptive)..... 6

ELT

Quantity	Luminaire (Luminous emittance)		
3	<div>DIALux - Stork Little Brother 27 W 16 LEDs SRL 027 730 L17 B016 SN DG1_O40_Bin-N2_TH Luminous emittance 1 Fitting: 1x16 LEDs bin N2 Absolute photometry Luminaire luminous flux: 3236 lm Power: 27.0 W Luminous efficacy: 119.9 lm/W  Colourimetric data 1x: CCT 3000 K, CRI 72</div>	<div>See our luminaire catalog for an image of the luminaire.</div>	
2	<div>DIALux - Stork Little Brother 27 W 16 LEDs SRL 027 730 L17 B016 SN DG1_O40_Bin-N2_TH Luminous emittance 1 Fitting: 1x16 LEDs bin N2 Absolute photometry Luminaire luminous flux: 3236 lm Power: 27.0 W Luminous efficacy: 119.9 lm/W  Colourimetric data 1x: CCT 3000 K, CRI 72</div>	<div>See our luminaire catalog for an image of the luminaire.</div>	

Total lamp luminous flux: 16180 lm, Total luminaire luminous flux: 16180 lm, Total Load: 135.0 W, Luminous efficacy: 119.9 lm/W

Site 1




Maintenance factor: 0.80

Surface result objects

	Surface	Result	Average (Target)	Min	Max	Min/average	Min/max
1	Piebraucamais ceļš	Perpendicular illuminance (adaptive) [lx]	12.3	2.41	25.5	0.20	0.09
		Luminance [cd/m²]	0.78	0.15	1.62	0.19	0.09
2	NAI iekārtu laukums	Perpendicular illuminance (adaptive) [lx]	11.5	1.93	23.5	0.17	0.08
		Luminance [cd/m²]	0.54	0.09	1.11	0.17	0.08


Piebraucamais ceļš / Perpendicular illuminance (adaptive)



Maintenance factor: 0.80



**Piebraucamais ceļš: Perpendicular illuminance (adaptive) (Surface)**  
**Light scene: Light scene 1**  
Average: 12.3 lx, Min: 2.41 lx, Max: 25.5 lx, Min/average: 0.20, Min/max: 0.09

Isolines [lx]




Scale: 1 : 500

False colours [lx]




Scale: 1 : 500

Value grid [lx]



Scale: 1 : 500


**NAI iekārtu laukums / Perpendicular illuminance (adaptive)**

Maintenance factor: 0.80

**NAI iekārtu laukums: Perpendicular illuminance (adaptive) (Surface)**


**Light scene: Light scene 1**

Average: 11.5 lx, Min: 1.93 lx, Max: 23.5 lx, Min/average: 0.17, Min/max: 0.08

**Isolines [lx]**


Scale: 1 : 200

False colours [lx]



Scale: 1 : 200

Value grid [lx]



Scale: 1 : 200